



## DATA SHEET - OPTICSHIELD NANO

**OPTICSHIELD NANO is a crystal clear PPF using superior topcoat technology,** the most advanced on the market, to provide extra durability and easy workability with outstanding environmental resistance and antifouling.

**OPTICSHIELD NANO is a HI-CLEAR PPF focused on self-healing following the same formulation of our basic line.** You can enjoy enhanced workability with excellent elongation, easy repositioning & removal on the installation.



PET Protection Film (50 µm)

Protection Film (10 µm)

Non Yellowing TPU (145 µm)

Adhesive (40 µm)

Release Liner (80 µm)

### FEATURES AND STRUCTURES

- > Fast Recovery Self-Healing
- > Anti-Fouling
- > Highest Transparency & Gloss
- > Water Repellency
- > Anti-Contamination
- > Non-Yellowing
- > Anti-Solvent
- > Excellent Adhesion Finish
- > Easy to Install

### WARRANTY

OPTICSHIELD NANO has an **10 year warranty** for yellowing, bubbling, and cracking. This is an excellent choice for the long-term protection of your car.

PROPERTY	TYPICAL VALUE	TEST METHOD
Thickness	195 µm (+-10 µm)	
Gloss (60°)	> 80 GU	FLK-3009
Peel strength	1.07 (+-0.3) kgf/inch	FLK-3001
Tensile Strength	2.6 (+-0.3) kgf/inch	FLK-3005
Elongation at break	110 % (+-10)	FLK-3003
Self Healing speed (1kg)	120 (±120) sec.	FLK-3005
Self Healing speed (with heat)	20 (±20) sec.	FLK-3005
Yellowing	500 hrs.	FLK-3015